FIRECHIEF®
AUTOMATIC POWDER EXTINGUISHERS

FIRECHIEF®
making the world a safer place



APS1/S APS2/S



APS12 APS10



APS6 APS2 APS1

MODEL:

APS1
APS2
APS6
APS10
APS12
APS1/S
APS2/S

- Designed for use in enclosed areas i.e. engine/plant rooms, switch rooms etc
- Fitted with pressure gauge for easy routine checking
- Stored pressure
- Fixing brackets included with extinguishers
- Supplied with 68°C red bulb
- 2 year guarantee

+44 (0) 330 999 0019
sales@firechiefglobal.com
firechiefglobal.com

FIRECHIEF®
AUTOMATIC POWDER EXTINGUISHERS

FIRECHIEF®
making the world a safer place

The Firechief® Automatic Powder Fire Extinguishers are designed for enclosed areas such as engine/plant rooms etc.

Containing ABC dry powder extinguishant which covers most fires involving wood/paper, flammable liquids and electrical fires. The heat-sensitive glass bulb bursts when the temperature rises to 68°C.

MODEL:

APS1
APS2
APS6
APS10
APS12
APS1/S
APS2/S



Specifications

Model	APS1	APS2	APS6	APS10	APS12	APS1/S	APS2/S
Product Code	100-1004	100-1008	100-1010	100-1006	100-1007	100-1588	100-1589
Description	Firechief® 1kg ABC Dry Powder Automatic Extinguisher	Firechief® 2kg ABC Dry Powder Automatic Extinguisher	Firechief® 6kg ABC Dry Powder Automatic Extinguisher	Firechief® 10kg ABC Dry Powder Automatic Extinguisher	Firechief® 12kg ABC Dry Powder Automatic Extinguisher	Firechief® 1kg ABC Dry Powder Automatic Extinguisher - Slimline	Firechief® 2kg ABC Dry Powder Automatic Extinguisher - Slimeline
Capacity (kg)	1	2	6	10	12	1	2
Fire Rating	n/a	n/a	n/a	n/a	n/a	n/a	n/a
MED Approval	NO	NO	NO	NO	NO	NO	NO
Coverage (m^2)	1	2	6	10	12	1	2
Recommended mounting height above risk (m)	1.5	1.5	2	2	2	1.5	1.5
Working Pressure (bar)	15	15	15	15	15	15	15
Temperature Range (°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)
Bulb release temp (°C)	68	68	68	68	68	68	68
Product Height (mm)	90	123	180	215	275	327	383
Product Diameter (mm)	160	190	250	270	270	85	110
Filled Weight (kg)	2.2	5.5	8.2	14	16.1	2.2	5.5
Carton Height (mm)	170	121	362	454	300	340	405
Carton Length (mm)	278	111	276	278	450	102	125
Carton Width (mm)	166	375	264	278	300	102	125
Packaged Weight (kg)	2.5	3.7	9.3	13.6	15.5	2	3.6
Product EAN	5055377901561	5055377901578	5055377901585	5055377901592	5055377901608	5055377961022	5055377961039

*Guidance coverage likely achieved using recommended mounting height.

For more information contact: Firechief® Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | **Imported into EU by:** Firechief® Global (EU) Ltd, 3rd Floor, 40 Mespil Rd, Dublin 4, D04 C2N4, Ireland

+44 (0) 330 999 0019 sales@firechiefglobal.com firechiefglobal.com

v1-01/11/24