FIRECHIEF® LEVER OPERATED NOZZLE

FIRECHIEF®
making the world a safer place

The lever operated nozzle is made from strong but lightweight aluminium alloy, resulting in an easy-to-use nozzle for professional firefighting applications. The lever operation gives a simple on/off control of flow. The 21/2" coupling is designed for use with 65mm layflat hosing.

MODEL:
AWG1-B

- Lever operated nozzle
- 2½" coupling
- Made from light alloy

Model	AWG1-B
Product Code	103-1087
Length (mm)	443
Width (mm)	143
Depth (mm)	89
Weight (kg)	1.59
Working Pressure (MPA)	0.8 - 1.6
Flow Rate (litre/min)	200 - 250
Throw Distance (m)	>22
Orifice Diameter (mm)	13



Imported into EU by: Firechief® Global (EU) Ltd, 3rd Floor, 40 Mespil Road, Dublin 4, D04 C2N4, Ireland
For more information contact: Firechief® Global, 3 Lands End Way, Oakham, Rutland, LE15 6RB, UK | UK: 0330 999 0019 | International: +44 (0)1572 772657 | www.firechiefglobal.com/contact-us/

+44 (0) 330 999 0019 sales@firechiefglobal.com firechiefglobal.com

v1-30/05/25