STORAGE VAULTS

UK manufactured

3 YR GUARANTEE

SAFETY NOTE

Before storage of herbicides & petroleum based products takes place the advice of the following should be sought for specific guidance.

- Health & Safety Inspector
- Trading Standards Officers
- Environmental Health Officers
- Fire Officers

SSV03Z

SSV02Z

Designed to comply with the Flammable Liquid Storage Regulations (1972) as appropriate & the Factory Inspection Guide HSG51

Adjustable vent meets the requirements of both flammable storage (vents closed) & agrochemicals (vents open)

All welded units conforming to the A.P.E.A. construction requirements

Provide a half hour protection from collapse & the passage of flame

Multi-lockable for high security & fitted with a lift up action lid assisted by gas struts

For extra protection & fork lifting the units have skids on the base

Middle shelves pivot on models SSV01Z & SSV02Z to enable larger items to be stored on the base level

Model SSV03Z has a central partition & four shelves - the two middle shelves fold away & the two top shelves are made in 3 sections - the back section is fixed in position & the front two sections removable

All models have a liquid-tight base to contain spillage

N.B. A Fork Lift will be needed to unload these vaults

Overall Size W x D x H mm	Liquid Tight Sealed Base Unit Capacity	Shelves mm	Weight kg	Model
700 x 850 x 1270	120 Litre	2 x Shelves: Top: 690 x 400 fixed Middle: 690 x 400 pivots	180	SSV01Z
1370 x 850 x 1270	250 Litre	2 x Shelves: Top: 1360 x 400 fixed Middle: 1360 x 400 pivots	260	SSV02Z
2500 x 1080 x 1270	550 Litre	4 x Shelves: 1220 x 500	460	SSV03Z