

Kenilworth Cycle Shelters Specification Sheet



Sizes Available:

<u>Height</u>	<u>Width</u>	<u>Depth</u>	<u>Bike Capacity</u>
2230mm	2150mm	2000mm	4 Bikes
2230mm	2150mm	3000mm	8 Bikes
2230mm	2150mm	4000mm	10 Bikes
2230mm	2150mm	5000mm	12 Bikes

Cycle Shelter Construction:

- The leg frames on this range of cycle shelters can either be bolted to the floor or grouted into the ground.
- Initial shelters can be linked side by side to form longer runs.
- Perspex curved roof and end panels.
- Manufactured from mild steel or galvanised steel.

Paint Finish:

- Three stage pre-treatment and phosphate coating.
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard antibacterial compound.
- Cycle Shelters available with various powder coated colour options.

QMP LTD, Timmis Road, Lye, Stourbridge, West Midlands, DY9 7BQ

Tel: 01384 899800


Fax: 01384 899801

Email: sales@qmp.uk.com

Website: www.qmp.uk.com

Cycle Shelter Colours:

Red	RAL 3003
Green	RAL 6028
Blue	RAL 5017
Black	RAL 9005
Light Grey	RAL 7035
Galvanised	-



Equipment Cleaning & Maintenance instructions:

- Clean paint work periodically with warm soapy water

QMP LTD, Timmis Road, Lye, Stourbridge, West Midlands, DY9 7BQ

Tel: 01384 899800

Fax: 01384 899801

Email: sales@qmp.uk.com

Website: www.qmp.uk.com