

Post Box Lockers



Sizes & Compartments Available

Sizes:

1325Hx230Wx255Dmm - 100 Series
 1075Hx230Wx255Dmm - 100 Series
 1725Hx300Wx380Dmm - 140 Series
 1230Hx300Wx380Dmm - 140 Series
 1665Hx300Wx380Dmm - 240 Series
 870Hx300Wx380Dmm - 240 Series

Door Compartment / Slot (mm) Options:

10 Compartments - 15mm Slots (100 Series)
 10 Compartments - 25mm Slots (140 Series)
 8 Compartments - 15mm Slots (100 Series)
 7 Compartments - 25mm Slots (140 Series)
 6 Compartments - 40mm Slots (240 Series)
 3 Compartments - 40mm Slots (240 Series)



Door Open Aperture:

100 Series has an aperture of 100x165mm with a 15mm post slot
 140 Series has an aperture of 140x235mm with a 25mm post slot
 240 Series has an aperture of 240x235mm with a 40mm post slot



Paint Finish

A three-stage pre-treatment and phosphate coating are applied.

Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180 deg, including our germ guard anti-bacterial compound.

The carcass is powder-coated - Light Grey RAL 7035.

Doors are powder-coated with a choice of Light Grey RAL 7035 or Blue RAL 5012.

Other door colours are available, however, these have a minimum order quantity of 8 units. Colours include Red RAL 3003, Green RAL 6024, Light Blue RAL 5012 & Yellow RAL 1018.



www.qmp.uk.com



01384 899800



sales@qmp.uk.com



Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).



Locker Construction

General Construction:

- 0.7mm mild steel, pop riveted carcass construction.
- Delivered as a fully assembled unit.
- Pre-drilled carcass for nesting lockers together to complete a run/bank.
- Each compartment has its own post slot.
- Greg facia plates with a slot above the lock, suitable for a number or name. These are only available on the 140 & 240 series.
- Fitted with standard master cam locks with 2,000 differs.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.

Locker Door Construction:

- Material: 0.7mm Mild Steel. The door is attached by a 7mm hinge bar running from top to bottom and fitted with 10 disc key operated cam lock with 2,000 differs.



Replacement Locks & Spare Keys

Replacement locks and keys are available from QMP.
Replacement keys are available from Fast Key Ltd.
www.fastkeys.co.uk - sales@fastkeys.co.uk.



Delivery

All sizes and compartment options are manufactured-to-order item and will be on an extended lead-time.



**Our live chat satisfaction rating,
based on user feedback**

